

# PRIMER 52

Adhesive primer for improved grip

## DESCRIPTION

PRIMER 52 is a solventfree primer applied on waterborn polymer coatings prior to the application of plasterbased or cementbased products or on smooth mineral substrates in order to improve adhesion of finishing coatings.

Typical uses:

- » For the improved adhesion of plasterboards by dot&dab on Blowerproof® Liquid or Brush.
- » For the improved adhesion of finish plaster on Blowerproof® Liquid or Brush.
- » For the improved adhesion of the Rockwool mortar "REDArt CAPA BASE CASA" or similar mortars.
- » For the improved adhesion of waterborn polymer coatings on metals, fixings, mastics.

## APPLICATION

Remove dust from the substrate.  
Apply PRIMER 52 by roller or paintbrush.  
Apply only 1 layer, approximately 200 gr/m2.  
Allow to dry before application of the next products.

## TECHNICAL DATA

- » Liquid
- » Density (kg/l): 1,2 – 1,3
- » pH: 9,0 (Ind.)
- » Shelflife :12 months in un-opened packaging and if stored properly. Protect against frost.
- » Harmfull according 1999/45/EG: no.

Application :

- » Do not dilute
- » Mix before use
- » Minimal application temperature : +5° C.
- » To be applied between +5° C to +35° C.
- » Do not apply in sunlight.
- » Clean tools with water.

## PACKAGING

5kg – Eupallet: 96 x 5kg  
10kg – EUpallet: 60 x 10kg

## SAFETY

PRIMER 52 is not harmful according current regulation. Nevertheless it is recommended to follow the guidelines for using chemical products. Consult the safety datasheet prior to starting the application.

DATE OF THIS EDITION: 23/07/2021

Our general conditions of sale apply. This document does not have a contractual value. This technical data sheet replaces and annuls the previous edition. The information given in this sheet has the purpose to inform and advice you. At every moment, this sheet can be adapted because of technical evolution. All information is given in good faith and without any warranty. The application, use and processing of these products are beyond our control and therefore the entire responsibility of the user/client/applicator. The user of the product must test the product's suitability and apply for the intended purpose. Established liability if any for any reason is always limited to the value of the goods supplied by HEVADEX bvba. The products and systems are manufactured under total quality management. HEVADEX bvba reserves the right to change the properties of its products. Users must always refer to the most recent issue of the local Product Data Sheet, copies of which will be supplied on request.